RoughMark



Concept® 285 RoughMark™ is a 3.5 mil matte opaque polymeric vinyl film coated with a high-tack removable (HTR) acrylic pressure sensitive adhesive on a 90# layflat liner. The 90# liner provides excellent dimensional stability for digital printing. Concept® 285 accepts a variety of solvent-based, eco-solvent, latex and *UV curable inks common to wide format digital printing systems.

Applications Concept® 285 RoughMark™ can be used in applications where a conformable

removable vinyl is desired. This film conforms well with controlled heat and features clean removability from a variety of moderately textured substrates including brick, block, and concrete surfaces (vertical application only). If a high gloss finish is desired, it is

recommended to use Concept® 242 gloss clear cast laminate.

<u>NOTE:</u> If applied to a painted surface the paint must bond tightly to the substrate. Test all applications prior to use. Not designed for coated/ sealed/ treated stainless steel, brass

or bronze surfaces

Thickness Film 3.5 mils.

Adhesive 1.8 to 2.1 mils. Liner 6.5 mils.

(Thickness variation +/- 10%)

Temperature Ranges Minimum application temperature +40°F.

Service temperature -40° F to +200 F.

Removability Removable up to 6 months for common substrates under normal exposure conditions.

Adhesion Stainless steel 16 Oz/ inch minimum

PSTC-101 Method A

Dwell is 24 hours at room temperature.

Solvent Resistance Good resistance to intermittent exposure from petroleum oils, grease, aliphatic

hydrocarbons and gasoline.

Water Resistance Excellent. Humidity Resistance Excellent.

Storage Stability One year shelf life stored at 70° F and 50% relative humidity.

Recommendations Completely evaporate inkjet solvents before application. Failure to do so may facilitate

solvent penetration resulting in vinyl degradation. * For UV Curable inks, please consult

with the ink manufacturer for specifics on ink flexibility.

Product Codes 285-54 54" x 150'

285-5475 54" x 75' **285-60** 60" x 150' **285-6075** 60" x 75'



Manufacturer of Pressure Sensitive Films, Traffic Graffic Floor Advertising Films, Custom Coatings and Printing Inks.